

9/4 RM Motor

Key Features

- Compact powerful 2" tubular motor
- Torque rating of 40 Nm (350 inch-pounds)
- Fully encapsulated, shock resistant motor coil, high moisture resistance and fire protection ratings
- Fully compatible with all Elero-Matic automatic controllers
- Easy limit setting



The Elero 9/4 tubular motor exceeds the 9/3.3 motor by 61 inch-pounds of torque. It is ideally suited for heavy duty 2-inch operations. The 9/4 has a net 40 Nm torque rating of 350 inch-pounds and 12 rpm turning speed. This combination makes the 9/4 the ideal drive unit for shutters and awnings in the standard to medium size range. The Elero 9/4 has been designed for use in exterior applications in harsh climates due to its extra coil protection and the robust Elero design. The ease and reliability of the Elero limit switch system makes the 9/4 the ideal unit for all applications where reduced installation time and maintenance free operation are critical issues.

Technical Features

- 350 lb. lift from barrel
- 23" nominal length
- 29-turn limit range
- 40 Newton meters
- 12 rpm
- 240 watts
- 2.0 amps

Model and Item Numbers

9/4 Motor	31.242.0001
9/4 MO Motor	31.282.0002
9/4 /Tec™ Motor	91.242.0001

Dimensions

