

# Rolling Shutter Lift Capacity Chart

## Single Unit Shuttes with 3/8" (10mm) Thick Material

Model	Torque In. Lbs.	Tube OD (mm)	Shutter Length		
			5 Ft.	10 Ft.	15 Ft.
RM 9/1	87	60	40	31	27
RM 9/1.8	157	60	75	59	50
RM 9/2.5	217	60	105	84	71
RM 9/3.3	289	60	140	111	95
RM 9/4	350	60	170	136	117
RM 9/1	87	70	36	30	25
RM 9/1.8	157	70	68	56	48
RM 9/2.5	217	70	95	80	70
RM 9/3.3	289	70	130	107	92
RM 9/4 or 11.4	350	70	155	130	115
RM 11/6	525	70	230	197	171
RM 11/8	700	70	310	264	226
RM 11/10	885	70	390	331	286
11/8 Tandem	1400	70	603	522	456
11/10 Tandem	1770	70	754	653	571
RM 11/6	525	100	185	173	155
RM 11/8	700	100	249	232	209
RM 11/10	885	100	312	290	262
RM 15/15	1062	100	375	350	315
RM 15/18	1274	100	450	420	380
RM 15/23	1637	100	580	526	487
11/8 Tandem	1400	100	496	460	421
11/10 Tandem	1770	100	620	575	526

This chart is intended for use as a guide only. Actual torque requirements may vary. Please consult your Elero representative for further assistance.

# Rolling Shutter Lift Capacity Chart

## Single Unit Shuttles with 1/2" (12mm) Thick Material

Model	Torque In. Lbs.	Tube OD (mm)	Shutter Length		
			5 Ft.	10 Ft.	15 Ft.
RM 9/1	87	60	37	30	25
RM 9/1.8	157	60	60	54	48
RM 9/2.5	217	60	95	76	65
RM 9/3.3	289	60	126	100	85
RM 9/4	350	60	152	121	103
RM 9/1	87	70	35	29	24
RM 9/1.8	157	70	64	52	45
RM 9/2.5	217	70	88	74	63
RM 9/3.3	289	70	117	97	84
RM 9/4 or 11.4	350	70	141	117	103
RM 11/6	525	70	212	176	155
RM 11/8	700	70	282	235	206
RM 11/10	885	70	353	294	259
11/8 Tandem	1400	70	565	469	405
11/10 Tandem	1770	70	707	587	507
RM 11/6	525	100	183	161	143
RM 11/8	700	100	245	214	191
RM 11/10	885	100	305	268	239
RM 15/15	1062	100	367	322	286
RM 15/18	1274	100	441	386	343
RM 15/23	1637	100	563	493	439
11/8 Tandem	1400	100	490	428	382
11/10 Tandem	1770	100	612	535	477

This chart is intended for use as a guide only. Actual torque requirements may vary. Please consult your Elero representative for further assistance.